\20 ANTIMICROBIAL Protection film Technical Data Sheet

July 2020



This grade is equipped with proprietary antimicrobial additive especially designated for antimicrobial application.

Applications

It is designated for antimicrobial purpose on high-touch surfaces, example: touch screen, lift button, shopping cart armrest, door handle, stair handrail and ATM display touch panel.

Antimicrobial Efficacy Test

Please find the attached ALS (Australia Laboratory Services) and SGS testing results for 1 hour, 4 hours and 24 hours contact time.

Physical Properties

Thickness Length Width Color

120micron 1m 300mm Transparent clear

Application Period

Up to 6 months or when it is torn, scratched or hazed due to contamination, whichever is earlier.

Storage Conditions

Recommended storage's conditions are 25 °C, 75% RH with good air ventilation.

Disclaimer

ADTECH MALAYSIA makes no other warranties, express or implied, including, but no limited to, any implied warranty of merchantability or fitness for a particular purpose or any implied warranty arising out of a course of dealing, customer or usage of trade. The user is responsible to determine if ADTECH MALAYSIA product is fit for their application and usage.

Except where prohibited by law, ADTECH MALAYSIA will NOT be liable for any loss or damage arising from ADTECH MALAYSIA product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ADTECH MALAYSIA SDN. BHD. (636504-X)

No. 33, Jalan Koporat /KU9, Taman Perindustrian Meru, 42200 Klang, Selangor, Malaysia. T: +603-3393 6933 F: +603-3393 4388 E: sales@adtechmy.com W: www.adtechmy.com











